

电鼓
Electric



型号/MODEL	BLC-6005-E
电压/PRESSURE	230V
规格/SPECIFICATION	2G 0.75mm ² - 3G 1.5mm ²
输入线/INPUT LINE	1.0m(L)
输出线/OUTPUT LINE	5m/8m/10m(L)
包装尺寸/PACKING DIMENSION	26.5x10x25.5cm
净重/N.W	2KG
毛重G.W	2.5KG

气鼓
Air



型号/MODEL	BLC-6005-A
管质/HOSE MATERIAL	PU夹纱/PUmesh
规格/SPECIFICATION	Φ5/Φ6.5mm
输入管/INPUT HOSE	1.0m(L)
输出管/OUTPUT HOSE	5m/8m/10m(L)
工作压力/WORKING PRESSURE	10BAR
爆破压力/BURST PRESSURE	30BAR
包装尺寸/PACKING DIMENSION	26.5x10x25.5cm
净重/N.W	2KG
毛重G.W	2.5KG

灯鼓
Light



型号/MODEL	BLC-6005-L
额定功率/PEAKE LOAD	6W
规格/SPECIFICATION	2G 0.75mm ²
输入线/INPUT LINE	1.0m(L)
输出线/OUTPUT LINE	5m/8m/10m(L)
包装尺寸/PACKING DIMENSION	26.5x10x25.5cm
净重/N.W	2KG
毛重G.W	2.5KG

电鼓
Electric



型号/MODEL	BLC-6006-E
电压/PRESSURE	230V
规格/SPECIFICATION	2G 1.5mm ² - 3G 2.5mm ²
输入线/INPUT LINE	1.0m(L)
输出线/OUTPUT LINE	10m/12m/15m/20m(L)
包装尺寸/PACKING DIMENSION	44.5x17.7x37.7cm
净重/N.W	4.2KG
毛重G.W	4.5KG

气鼓
Air



型号/MODEL	BLC-6006-A
管质/HOSE MATERIAL	PU夹纱/PUmesh
规格/SPECIFICATION	Φ8/Φ10/Φ12mm
输入管/INPUT HOSE	1.0m(L)
输出管/OUTPUT HOSE	10m/12m/15m/20m(L)
工作压力/WORKING PRESSURE	18BAR
爆破压力/BURST PRESSURE	60BAR
包装尺寸/PACKING DIMENSION	44.5x17.7x37.7cm
净重/N.W	4.2KG
毛重G.W	4.5KG

灯鼓
Light



型号/MODEL	BLC-6006-L
额定功率/PEAKE LOAD	60W
规格/SPECIFICATION	2G 1.5mm ²
输入线/INPUT LINE	1.0m(L)
输出线/OUTPUT LINE	10m/12m/15m/20(L)
包装尺寸/PACKING DIMENSION	44.5x17.7x37.7cm
净重/N.W	4.2KG
毛重G.W	4.5KG

水鼓
Water



型号/MODEL	BLC-6006-W
管质/HOSE MATERIAL	PVC夹纱/PVCcmesh
规格/SPECIFICATION	Φ8x12 3/8mm
输入管/INPUT HOSE	1.0m(L)
输出管/OUTPUT HOSE	10m/12m/15m(L)
工作压力/WORKING PRESSURE	6BAR
爆破压力/BURST PRESSURE	60BAR
包装尺寸/PACKING DIMENSION	42x17x34cm
净重/N.W	4.2KG
毛重G.W	4.5KG

电鼓

Electric



型号/MODEL	BLC-6002-E
电压/PRESSURE	230V
规格/SPECIFICATION	2G 1.5mm ² -3G2.5mm ²
输入线/INPUT LINE	1.0m(L)
输出线/OUTPUT LINE	12m/15m/20m(L)
包装尺寸/PACKING DIMENSION	44.5x19.5x39.5cm
净重/N.W	4.2KG
毛重G.W	4.5KG

气鼓

Air



型号/MODEL	BLC-6002-A
管质/HOSE MATERIAL	PU夹纱/PUmesh
规格/SPECIFICATION	Φ8/Φ10/Φ12mm
输入管/INPUT HOSE	1.0m(L)
输出管/OUTPUT HOSE	10m/12m/15m/20m(L)
工作压力/WORKING PRESSURE	18BAR
爆破压力/BURST PRESSURE	60BAR
包装尺寸/PACKING DIMENSION	44.5x19.5x39.5cm
净重/N.W	4.2KG
毛重G.W	4.5KG

灯鼓

Light



型号/MODEL	BLC-6002-L
额定功率/PEAKE LOAD	6W
规格/SPECIFICATION	2G 1.5mm ²
输入线/INPUT LINE	1.0m(L)
输出线/OUTPUT LINE	12m/20m/25m(L)
包装尺寸/PACKING DIMENSION	44.5x19.5x39.5cm
净重/N.W	4.2KG
毛重G.W	4.5KG

水鼓

Water



型号/MODEL	BLC-6002-W
管质/HOSE MATERIAL	PVC夹纱/PVCcmesh
规格/SPECIFICATION	Φ8/Φ10mm
输入管/INPUT HOSE	1.0m(L)
输出管/OUTPUT HOSE	10m/12m/15m(L)
工作压力/WORKING PRESSURE	6BAR
爆破压力/BURST PRESSURE	24BAR
包装尺寸/PACKING DIMENSION	44.5x19.5x39.5cm
净重/N.W	4.2KG
毛重G.W	4.5KG

电鼓

Electric



型号/MODEL	BLC-6003-E
电压/PRESSURE	230V
规格/SPECIFICATION	2G 1.5mm ² -3G2.5mm ²
输入线/INPUT LINE	1.0m(L)
输出线/OUTPUT LINE	15m/20m/30m(L)
包装尺寸/PACKING DIMENSION	42x17x34cm
净重/N.W	4.2KG
毛重G.W	4.5KG

气鼓

Air



型号/MODEL	BLC-6003-A
管质/HOSE MATERIAL	PU夹纱/PUmesh
规格/SPECIFICATION	Φ8/Φ10/Φ12mm
输入管/INPUT HOSE	1.0m(L)
输出管/OUTPUT HOSE	15m/20m/30m(L)
工作压力/WORKING PRESSURE	18BAR
爆破压力/BURST PRESSURE	60BAR
包装尺寸/PACKING DIMENSION	42x17x34cm
净重/N.W	4.2KG
毛重G.W	4.5KG

灯鼓

Light



型号/MODEL	BLC-6003-L
额定功率/PEAKE LOAD	6W
规格/SPECIFICATION	2G 1.5mm ²
输入线/INPUT LINE	1.0m(L)
输出线/OUTPUT LINE	15m/20m/25m/30m(L)
包装尺寸/PACKING DIMENSION	42x17x34cm
净重/N.W	4.2KG
毛重G.W	4.5KG

水鼓

Water



型号/MODEL	BLC-6003-W
管质/HOSE MATERIAL	PV夹纱/PUcmesh
规格/SPECIFICATION	Φ8/Φ10mm
输入管/INPUT HOSE	1.0m(L)
输出管/OUTPUT HOSE	15m/20m/25m(L)
工作压力/WORKING PRESSURE	6BAR
爆破压力/BURST PRESSURE	24BAR
包装尺寸/PACKING DIMENSION	42x17x34cm
净重/N.W	4.2KG
毛重G.W	4.5KG

电鼓
Electric



型号/MODEL	BLC-6009A-E
电压/PRESSURE	230V
规格/SPECIFICATION	2G 1.5mm ² -3G2.5mm ²
输入线/INPUT LINE	1.0m(L)
输出线/OUTPUT LINE	10m/12m/15m/20m(L)
包装尺寸/PACKING DIMENSION	37x18.2x36.5cm
净重/N.W	4.2KG
毛重G.W	4.5KG

气鼓
Air



型号/MODEL	BLC-6009A-A
管质/HOSE MATERIAL	PU夹纱/PUmesh
规格/SPECIFICATION	Φ8/Φ10/Φ12mm
输入管/INPUT HOSE	1.0m(L)
输出管/OUTPUT HOSE	10m/15m/20m(L)
工作压力/WORKING PRESSURE	15BAR
爆破压力/BURST PRESSURE	60BAR
包装尺寸/PACKING DIMENSION	37x18.2x36.5cm
净重/N.W	4.2KG
毛重G.W	4.5KG

灯鼓
Light



型号/MODEL	BLC-6009A-L
额定功率/PEAKE LOAD	6W
规格/SPECIFICATION	2G 1.5mm ²
输入线/INPUT LINE	1.0m(L)
输出线/OUTPUT LINE	10m/20m/25m/30m(L)
包装尺寸/PACKING DIMENSION	37x18.2x36.5cm
净重/N.W	4.2KG
毛重G.W	4.5KG

水鼓
Water



型号/MODEL	BLC-6009A-W
管质/HOSE MATERIAL	PVC夹纱/PVCcmesh
规格/SPECIFICATION	Φ8/Φ10 mm
输入管/INPUT HOSE	1.0m(L)
输出管/OUTPUT HOSE	10m/12m/15m(L)
工作压力/WORKING PRESSURE	6BAR
爆破压力/BURST PRESSURE	24BAR
包装尺寸/PACKING DIMENSION	37x18.2x36.5cm
净重/N.W	4.2KG
毛重G.W	4.5KG

电鼓
Electric



型号/MODEL	BLC-7009-E
电压/PRESSURE	230V
规格/SPECIFICATION	2G 1.5mm ² -3G2.5mm ²
输入线/INPUT LINE	1.0m(L)
输出线/OUTPUT LINE	10m/12m/15m(L)
包装尺寸/PACKING DIMENSION	37x18.2x36.5cm
净重/N.W	4.2KG
毛重G.W	4.5KG

气鼓
Air



型号/MODEL	BLC-7009-A
管质/HOSE MATERIAL	PU夹纱/PUmesh
规格/SPECIFICATION	Φ8/Φ10/Φ12mm
输入管/INPUT HOSE	1.0m(L)
输出管/OUTPUT HOSE	10m/12m/15m(L)
工作压力/WORKING PRESSURE	18BAR
爆破压力/BURST PRESSURE	60BAR
包装尺寸/PACKING DIMENSION	37x18.2x36.5cm
净重/N.W	4.2KG
毛重G.W	4.5KG

灯鼓
Light



型号/MODEL	BLC-7009-L
额定功率/PEAKE LOAD	60W
规格/SPECIFICATION	2G 1.5mm ²
输入线/INPUT LINE	1.0m(L)
输出线/OUTPUT LINE	10m/12m/15m(L)
包装尺寸/PACKING DIMENSION	37x18.2x36.5cm
净重/N.W	4.2KG
毛重G.W	4.5KG

水鼓
Water



型号/MODEL	BLC-7009-W
管质/HOSE MATERIAL	PVC夹纱/PVCcmesh
规格/SPECIFICATION	Φ8/Φ10 mm
输入管/INPUT HOSE	1.0m(L)
输出管/OUTPUT HOSE	10m/12m/15m(L)
工作压力/WORKING PRESSURE	6BAR
爆破压力/BURST PRESSURE	24BAR
包装尺寸/PACKING DIMENSION	37x18.2x36.5cm
净重/N.W	4.2KG
毛重G.W	4.5KG